

技术参数

取样方式 Sampling method	静态截取式 Static interception	
采样容器 sampling container	定容采样瓶 (溶解油层) Fixed volume sampling bottle (dissolved oil layer)	油膜采集瓶 (油膜层、乳浊层) Oil film collection bottle (oil film layer, opacification layer)
采样容器容量 Sampling container capacity	500ml (特殊规格可定制) 500ml (special specifications can be customized)	1 ~ 5L (特殊规格可定制) 1 ~ 5L (special specifications can be customized)
采样瓶误差 Sampling bottle error	定容瓶容量误差: $\leq 5\%$ Fixed volume bottle capacity error: $\leq 5\%$	油膜瓶内径误差: $\leq \pm 5\%$ Oil film bottle inner diameter error: $\leq \pm 5\%$
采样容器系数 k Sampling container coefficient k	0.675、1.0 ~ 5.0	
采集深度 Collection depth	液面下 (300 ~ 500) mm Below the liquid surface (300~500) mm	(10 ~ 150) mm
操作方式 Operation mode	Ai 全自动控制 AI fully automatic control	
工作电压 Working voltage	24VDC	
工作环境温度 Working environment temperature	0°C ~ 50°C	
工作环境湿度 Working environment humidity	$\leq 85\%RH$	
外形尺寸 (高 × 宽 × 深)	270mm × 250mm × 930mm	

Overall dimensions (height × width × depth)	
重量 weight	≤8kg
功耗(平均) Power consumption (average)	5W